




The People You Know. The Products You Trust.



SuperVac Gale Force™

4.8 Cubic Yard Parking Area Sweeper

*Sweeper shown with optional equipment






- Increased Water Capacity
- Extended 6'6" Dumping Height
- WhisperWheel Fan Technology
- Large Separate Cleanout Door

Quality	Performance	Public Safety	Value	Customer Support

800.879.7933

www.schwarze.com



*TYPICAL MEASUREMENTS SHOWN, EXACT DIMENSIONS DEPENDING ON OPTIONS AND TRUCK MANUFACTURER

WEIGHTS AND DIMENSIONS

Total empty weight	10,480 lb (4753.64 kg)
Overall width	85 in (2159 mm)
Overall length	238 in (6045 mm)
Overall height	99 in (2515 mm)
Wheelbase	132.5 in (3365 mm)
Turning radius	20 ft curb to curb
Sweeping width (Head only)	82 in (2083 mm)
Sweeping width (Single broom)	103 in (2617 mm)
Sweeping width (Dual broom)	124 in (3150 mm)

AUXILIARY ENGINE

Make	Yanmar diesel
Model	4TNV98C-NYEM
Horse power	68 hp (50.4 kw)
Displacement	202.5 cu in (3319 cm ³)
Cooling	Liquid cooled
Alternator	12 volt; 55 amp
Safety shutdown	Three-point automatic
Air filter	2 element w/ precleaner
Oil filter	Full-flow spin-on

DEBRIS HOPPER

Construction	A36 carbon steel (Stainless steel optional)*
Dumping	Hydraulic to the rear
Dump door	Twin cylinder hydraulic
Inspection doors	1 x per side (10 in x 24 in)
Controls	In cab
Dumping height	77 in
Dump angle	88 degrees
Dust separator	Centrifugal
Intake tube	Bolt-in AR steel

DUST CONTROL SYSTEM

Pump	Heavy duty electric diaphragm
Capacity	130 gal (Diesel chassis) 65 gal (Gas chassis)
Tank construction	Polyethylene
Filtration	Cleanable 50 mesh filter
Nozzles	Hopper; pickup head; side broom
Optional tank	45 gal

TOOL STORAGE

Location	Two at rear of sweeper
Capacity	17.25 cu ft (0.489 m ³)
Latches	Lockable and adjustable
Shovel rack	2 x 2 inch tubes side to side

SAFETY EQUIPMENT

- Hopper safety props
- 4 way LED flashing lights
- Dual rear facing strobes
- Rear view camera system
- Back-up alarm
- Optional: strobes; beacons; arrow boards

SWEEPER WARRANTY

- 12 months / 1200 hours
- 60 month limited on hydraulics

PAINT

Hopper	DuPont Imron Elite
Underbody	Textured black urethane

PICKUP HEAD

Type	Blast to suction lateral transfer
Suction side	Left (Driver side)
Suspension	4 x adjustable springs
Construction	Single piece A36 steel formed channel
Width	82 in (2083 mm)
Suction diameter	10 in (254 mm)
Blast diameter	10 in (254 mm)
Skids	Carbide on adjustable side plates
Rubber flaps	2 x front; 1 x rear

SIDE BROOM

Type	Vertical steel digger
Diameter	39 in (991 mm)
Drive	Direct-drive hydraulic torque motor
Speed	Variable
Segments	4 x bolt-on disposable

HYDRAULIC SYSTEM

Type	Fixed-displacement gear pump
Capacity	15 gal (57 L)
Drive	Direct mount to engine
Filtration	10 micron element
Hoses	Rough-service double wire

CONTROL SYSTEM

Location	In cab
Switches	Heavy-duty rocker
Labeling	International symbol
Throttle	Electronic
Vacuum enhancer	Electric actuator with indicator
Gauges	Tachometer; hour-meter; oil pressure; water temperature

FAN SYSTEM

Design	WhisperWheel™
Diameter	30 in (762 mm)
Type	Radial pressure backward incline
Drive	Banded belt
Construction	Hardox AR steel
Balance	Less than 1.5 grams
Housing liner	Bolt-in corded rubber

CHASSIS (PRIMARY)

Make	Isuzu
Model	NPR HD
Type	Cab-over engine (COE)
GVWR/GCWR	14,500 lb / 20,500 lb (5152 kg / 9298 kg)
Engine	Diesel 215 hp turbo charged 4HK1-TC
Transmission	6 speed automatic with double overdrive
Frame	11.89 cu in section modulus
Tires	215/85R-16E (10 ply)
Wheels	6 hole steel disc
Brakes	Vacuum / hydraulic with 4 channel ABS
Steering	Integral hydraulic with tilt & telescopic
Electrical	12 volt
Alternator	140 amp
Batteries	Dual 750 cca
Exhaust	Vertical

Note: design and specifications subject to change without notice.

SuperVac
Gale Force

*Ask us about our optional:



Affiliates:



Schwarze Industries, Inc.
1055 Jordan Road
Huntsville, AL 35811
800.879.7933
An Alamo-Group Company

